SUBMITTAL RECORD	
JOB	
LOCATION	
SUBMITTED TO	
SUBMITTAL PREPARED BY	_
APPROVED BY	
DATE	



## **Submittal Form Kwik-Twists**

### DESCRIPTION

When preparing to suspend HVAC equipment, ductwork or accessories, threaded anchor points are often required. Kwik-Twists from Rize are side or vertical mounted fasteners that provide attachment points for steel threaded rods and other assemblies. There are two variations of Kwik-Twists; one for penetrating and threading into steel and one for wood. Each Kwik-Twist has a 3/8"-16 threaded hole in the fastener's hex shaped head. Side mounted Kwik-Twists have the threaded hole perpendicular to the fastener shaft and passing completely through the fastener head. Vertical mounted Kwik-Twists have the threaded hole parallel to the fastener shaft and as deep as the fastener head.

# Wood






**Wood Driver** 

**Steel Driver** 

### **FEATURES**


- No pilot hole is needed for Kwik-Twists
- All fasteners are zinc plated for corrosion resistance
- Chucks sold separately for easy installation

### Wood



Install with appropriate sized wood socket driver.

## **Steel**



Install with appropriate sized steel socket driver.

Item #	Code	Description	Thread	Hang	Threaded Rod Size	Ultimate Tensile Load (lbs)	Packaged	
30294	SHW38	3/8" x 2" Wood Hanger Sidewinder	1 x 4" x 2"	Horizontal	3/8"	1,800	25/Ctn.	
30139	VHW38	3/8" x 2" Wood Hanger Vertical Winder	1 x 4" x 2"	Vertical	3/8"	1,510	25/Ctn.	
30295	SHS38	3/8" x 2" Steel Hanger Sidewinder	1/4-20	Horizontal	3/8"	3,530	25/Ctn.	
30140	VHS38	3/8" x 2" Steel Hanger Vertical Winder	1/4-20	Vertical	3/8"	2,375	25/Ctn.	
Driver sold separately.								

Please see our Rize testing and warnings webpage for the most detailed list of warnings: http://rizellc.com/techsupport-testing.html

Rize Enterprises, LLC

PO Box 1311 Brentwood, NY 11717 Tel: 631-930-7532 Fax: 631-249-8976

www.rizellc.com

